

Specification

C ³ V Series	2010	4005	6003
ELECTRIC			
AC input rating			
Voltage	85~264VAC		
Current	2.4A max./115VAC , 1.2A max./230VAC		
Frequency	47~63Hz		
Inrush	22A max./115VAC , 46A max./230VAC		
power factor	PF>0.95/230VAC , PF>0.99/115VAC		
ELECTRONIC			
DC output rating			
Voltage, Volt	0-20.00V	0-40.00V	0-60.00V
Current, Amp	0-9.990A	0-5.000A	0-3.500A
Power, Watt	200W	200W	210W
Line regulation			
CV, mV	<= 10mV	<= 10mV	<= 10mV
CC, mA	<= 5mA	<= 5mA	<= 5mA
Load regulation			
CV, mV	<= 10mV	<= 10mV	<= 10mV
CC, mA	<= 5mA	<= 5mA	<= 5mA
Ripple / Noise (*1)			
CV p-p, mV	<=30mVpp	<=30mVpp	<=30mVpp
CV rms, mV	<= 10mV	<= 10mV	<= 10mV
CC rms, mA	<= 10mA	<= 10mA	<= 10mA

MEASUREMENT			
Panel setting resolution			
Voltage, mV	10mV	10mV	20mV
Current, mA	5mA	2mA	2mA
Programming resolution			
Voltage, mV	10mV	10mV	20mV
Current, mA	5mA	2mA	2mA
Measurement accuracy			
Voltage, %	0.05 % +5 cnt	0.05 % +6 cnt	0.05 % +7 cnt
Current, %	0.2% + 10 cnt	0.1% +8 cnt	0.1% +8 cnt
Temperature coefficient			
Voltage	0.001%/°C	0.001%/°C	0.001%/°C
Current	0.005%/°C	0.005%/°C	0.005%/°C
PROTECTIONS			
OVP	yes	yes	yes
OCP	yes	yes	yes
OTP	yes	yes	yes
COMMUNICATION			
Interface: only 1 option			
RS232	DB9		
RS485	terminal block		
USB	type-B		
Protocol			
Data rate	57600/N/8/1		

NORMS	
EMC EMISSION	EN61000-3-2,-3
EMC IMMUNITY	EN61000-4-2,3,4,5,6,8,1
SAFETY	EN60950-1
ENVIRONMENT	
Operating temp.	0°C~50 °C
R.H., no condensed	20%~85%
Storage temp.	-20°C~70 °C
R.H., no condensed	<90%
PHYSICAL	
Dimensions/Weight	W*D*H = 100mm*250mm*40mm(<1U) / 1.2Kg
<p>*1: From output terminals, running a 25cm twisted wire pair terminated with a 0.1uf CC & 10uF EC, observe voltage across the capacitors under 20 MHz BW at full resistive load.</p>	



Trueful Electronics Co., Ltd.

真福電子股份有限公司 accuracy and efficiency

<http://www.trueful.com.tw>

Tel: 886-2-26922188

Fax:886-2-26922189

Eof.